

Industrial Washing Machine, Industrial Dry Cleaning Machine, Industrial Flat Work Iron, Industrial Hydro Extractor, etc.



SR SONS

laundry care system

Click To Whatsapp

Click To Call +91-9910904320, +91-9310969390

 \bigcirc

Click To Email



O'

About

INTRODUCTION

aundry care system

We are a Sole Proprietorship entity, affianced in Manufacturing, Wholesaler Trader And Service Provider an assorted range of Laundry Boiler, Washing Machine, Dry Cleaning Machine, Washer Extractor, etc.

Incorporated in the year 2011 of Delhi, (India), we "S.R. Sons Garments Equipment" are a Sole Proprietorship entity. We are Providing all Industrial Washing Machine's Repairing & Maintenance, our engineers are experts of this field lust 10 years. We also Manufacturing, Wholesaler and Trader an assorted range of Laundry Machine, Washing Machine, Dry Cleaning Machine, Washer Extractor, Laundry Finishing Machine And Equipment, Storage Trolley, etc. Under the excellent direction of our mentor "Vipin Saini (Proprietor)", we have attained a dynamic and remarkable position in this highly competitive industry.

OUR INFRASTRUCTURE

We have constructed hi-tech and the latest infrastructure facility that is incorporated with diverse sections such as warehousing & packaging section, production section, quality testing section, etc. Our highly advanced production section facilitates us to furnish the business activities in a peaceful and streamlined manner Constructed over an extensive area, our production department is supervised under the strict vigilance of our highly skilled team of professionals

REPAIR AND MAINTENANCE

We REPAIR AND MAINTENANCE all the LAUNDRY MACHINE such as Industrial Top & Front Loading washing Machine, Industrial Hydro Extractor Machine, Industrial Drying Tumbler Machine, Industrial Washer Extractor Industrial Dry cleaning Washing Machine (Automatic and Semi-automatic), Industrial Finishing Equipment, Industrial Flet Work Iron Machine(Calendar Machine), Industrial Flat bed Machine, Industrial Vacuum Finishing Table, Industrial Diesel Fired and Electric Steam Boilers (Automatic and Semi-automatic), Industrial Hot water Boiler, Industrial Soya Milk Boiler & All type Laundry equipments. We repair and maintenance all BRAND.

We also repair VFD, PLC. Also contact for YEARLY & MONTHLY MAINTENANCE. 24X7 Services with 100% guarantee.



SRS Industrial Washing Machine (Front Loading)

- Capable of washing all type and laundry linen.
- Complete stainless steel front & door.
- Inner Basket and outer drum-all highly polished stainless steel.
- Easy loading & unloading through large toughened glass door.
- The machine stops automatically on opening the door.
- Auto timed Auto reverse & forward.
- Auto digital temperature control. Auto Water Level Control.
- Easy to operate Space saving.
- Electric or Steam heated type.

Model	Capacity dry wt per Charge	Basket Size Volume	Wash Motor Extract Speed	Extract Motor Extract Speed	Main Door Opening	Consumption	Drain	Heating Steam Consumption	Electric Load	Overall Dimension WxDxH APP	Net wt/Shipping Wt. Shipping Size WxDxH App. Shipping Vol.
SRS F/15	15Kg.	810x410 211Lts	0.75Kw 35Rpm	1.50kw 200Rpm	500mm	1.0°BSP *100Lts/FILL	2°	0.5°BSP 15kg/hr	6Kw	950x1015x1500	550kg/700kg 1250x1300x1700 2.76M³
SRS F/30	30Kg.	960x500 362Lts	0.75Kw 35Rpm	2.25kw 200Rpm	500mm	1.0°BSP *125Lts/FILL	3°	0.5°BSP 25kg/hr	12Kw	1120x1450x150	840kg/700kg 1450x1740x1950 4.9M³
SRS F/60	60Kg.	1110x760 7351Lts	1.5Kw 35Rpm	3.75kw 200Rpm	650mm	1.0°BSP *250Lts/FILL	3º 3º	0.5°BSP 50kg/hr	24Kw 24Kw	1240x1800x1900	1100kg/1350kg 1550x2100x2120
SRS F/100	100Kg	1360x990 1437Lts	3.75Kw 25Rpm	5.5kw 150Rpm	800mm	1.0°BSP *500Lts/FILL	4° 4°	0.5°BSP 100kg/hr	36Kw	1520x2200x2100	1750kg/2050kg 1850x2500x2350 10.69M³

SRS Industrial Washing Machine (Side Loading)

- Electric, steam or thermal Fluid heated.
- Side Loading, open pocket, single & double door, ideal for larger laundries.
 Performs all type of wash with soap, detergent, bleaching, acid, stone, or any chemical wash including dying.
- Complete stainless steel Inner bosker & outer drum.
- Electricity & mechanically interlocked, S.S. Loading & Unloading doors.
- S.S. hopper & heater box "M.S trunnion shaft Epoxy painted structure frame.
- Electrical control well protected for performance auto timed, auto reverse & auto digital temperature control.
- Easy Protective device against single phasing, reverse phasing and motor overload.
 Front display of controls through pilot lamps, push bottons, etc. water level indication.
- Drive:- Heavy duty motor co-ordinates with heavy duty gear box to pully with belt toke the load.

	Capacity	Basket	Wash	Main Door Openin g	Water Connectio n Consumpti on APP	Drain	Heatin	ıg	Thermal Fluid	Overall	Net wt/Shipping Wt.
Model	dry wt Per Charge	Size Volume	Motor				Steam Connection Consumption	Electric Load	Connection Comsuption	Dimension WxDxH APP	Shipping Size WxDxH App. Shipping Vol.
SRS S/15	15Kg.	600x70 0 211Lts	0.37Kw	400X30 0	1.0°BSP *165Lts/FILL	2.5°	0.5°BSP 15kg/hr	6kw		1300x730x980	330kg/410kg 1600x1030x1280
SRS S/30	30Kg.	700x96 0 370Lts	0.75Kw	500X36 0	1.0°BSP *125Lts/FILL	2.5°	0.5°BSP 25kg/hr	12kw	1"x1"BSP 10000 Kcal/hr.	1560x890x1100	475kg/600kg 1860x1200x1400 3.1M³
SRS S/60	60Кд.	910x1130 1487Lts	1.5Kw	660X410	2.0°BSP *250Lts/FIL L	3.0°	1.0°B <mark>SP</mark> 50kg/hr	24kw	l"xl"BSP 20000 Kcal/hr.	2520x1300x120	1235kgx1525kg 2250x1400x1500 4.73M³
SRS S/100	100Kg	1200x151 0 1487Lts	3.75Kw	810X460	2.0°BSP *500Lts/FIL L	4.0°	1.0°BSP 100kg/hr	36kw	l"xl"BSP 40000 Kcal/hr.	2520x1300x135 0	1235kgx1525kg 2800x1600 6.9M³
SRS S/200	200Kg	1120x30 0 2954Lts	7.5Kw	810X460 2 Nos.	3.0°BSP *995Lts/FIL L	6.0°	1.0°BSP 200kg/hr	****	l"x1"BSP 80000 Kcal/hr.	4330x1300x135 0	3400kgx2575kg 4600x1600x1500 11.40M³
SRS S/400	400Kg	1360x40 0 5807Lts	1.5Kw	810X460 3 Nos.	4.0°BSP *2050Lts/FI LL	8.0°	1.5°BSP 400kg/hr	***	1"x1"BSP 160000 Kcal/hr.	6050x1700x175 0	4225kgx8850kg 6350x2050x1950 25.40M²



laundry care system



SRS Industrial Dry Cleaning Machine

aundry care system

- Front Loading, Open pocket, auto timed, auto reverse, auto filtration with low spin extract.
- Ideal for petrol solvent cleaning in the most efficient and economical manner with high quality results.
- Stainless steel basket & mild steel outer casing.
- Large lading & Unloading door Outer body duly painted.

	Capacity dry wt per Charge	Basket Size Volum e	Dry Cleaning Motor Speed	Extract Motor	Extract Motor	Filter Pump . Capacity	Tank Ca	pacity	Overall	Net wt/Shipping Wt. Shipping Size WxDxH App. Shipping Vol.
Model							Base	Filter	Dimension WxDxH APP	
SRS DC/15	15Kg.	700x47 0 180Lts	0.37Kw 35 RPM	1.5 Kw	200 RPM	0.37 KW 100Lts/Min	260 Lts	260 Lts.	1000x1080x17 30	475kg/545kg 1300x1380x1930 3.46M
SRS DC/30	30Kg.	960x50 0 362Lts	0.75Kw 35 RPM	3.75 Kw	200 RPM	0.37 KW 100Lts/Min	410 Lts	460 Lts.	1300x1250x20 00	900kg/115kg 1600x1500x22 5.45M

SRS Industrial Flat Work Iron

- Single or multi roller.
- Prematic raising & lowering of chests, rollers with moisture suction & variable speed.
- Auto timed & Auto temperature control.
- Powerful suction: Individual direct mounted centrifugal blower on to the roller quickly removes moisture.
- It offers a dramatic saving of time labour ideal for pressing of bed sheets, napkins, table lines, pillow cover and any type of flat line etc. made easy, failsafe finger guard stops the machine instantly.
- Electric or steam heated type.



Model	Roller Size Dia x Length	Drive Motor Suction Motor	Air Connection Consumption	Steam Connection Steam Consumption	Overall Dimension WxDXH APP	Net Wt/Shipping Wt.Shipping Size WxDXH App. Shipping Vol.
SRS H/18	450x210	1.0 Kw 0.75 Kw	θ15(0.5° BSP) 20 Lts/Min	θ15(0.5°BSP) 30 Kg/Hr	3000x1200x1400	1500Kg/1800kg 300x1500x1700 / 8.41M
SRS H/24	600x3000	2.25 Kw 0.75 Kw	015(0.5° BSP) 60 Lts/Min	θ15(0.5° BSP) 70 Kg/Hr	3800x1400x1600	2000Kg/12300Kg 41x1800x1900 / 140M
SRS H/30	830x3300	5.6 Kw 0.75 Kw	θ15(0.75° BSP) 60 Lts/Min	θ25(1° BSP) 150 Kg/Hr	4800x2200x1800	6950Kg/8150Kg 5100x3600x2000 / 36.72M
SRS H/32	830x3300	7.5 Kw 0.75 Kw	θ20(0.75° BSP) 200 Lts/Min	Ө38(1⁰ ВЅР) 300 Kg/Hr	4800x2200x1800	6950Kg/8150Kg 5100x3600x2000 / 36.72M





- Pneumatic operated bed with moisture and timer for bed releasing of head with pneumatic push butter raising and lowering of the head.
- Ideal for uniform, hosiery clothes, table lines, bed sheets and pillow covers.
- Press is fitted with a padded buck & polished iron head with moisture suctions features.
- Auto timed. Auto Temperature Control, Low energy consumption.
- Covered with teflon sheets in head.
- Electric or steam heated type.

Model	Head and Bed Size	Air Connection Consumption	The Fluid Connection Consumption	Connection Connection		Overall Dimension WxDxH APP	Net wt/Shipping Wt. Shipping Size WxDxH App. Shipping Vol.
SRS FBP/75	1500x750	0.5 BSP 100Lts/Min 6Kg/cm	0.5°, 0.5° BSP 16000 Kcal/hr	0.5° BSP 30Kg/hr	18Kw	1600x1600x1300	600Kg/800Kg 1900x1900x1600 5.77M
SRS FBP/110	2300x110	0.5 BSP 200Lts/Min 6Kg/cm	0.5°, 0.5° BSP 32000 Kcal/hr	0.5° BSP 60Kg/hr	36Kw	245x1950x1300	1150Kg/1500Kg 2750x2250x1600 9.9M

SRS Industrial Hydro Extractor

- Stainless steel basket "S.S Outer drum *Study welded construction facility to dismantle basket without dismantling the outer casing Electricity inte- rlocked top lid stops the machine when opened "Outer casing is moun- ded on M.S. heavy base frame, duly painted.
- Drive:- Directly mounted basket on a specially designed high torque, heavy duty motor with rests on the spigot of the base frame. Provided with built-in rubber buffer cushion to enable self balancing.
- No V-Belts "No loss of speed Quick self balancing Noiseless and Vibration-Free performance charge after charge.
- Electrically controlled instrumentation and protection for auto timing and automatic D.C. injection for braking. Protective devices single & reverse phasing and motor overload

Model	Capacity dry wt per Charge	Basket Size Volume	Motor	Basket Speed	Drain	Overall Dimansion WxDxH APP	Net Wt/Shipping Wt.Shipping Size WxDxH App. Shipping Vol.
SRS H/5	15Kg.	550x300 71 Lts	1000RPM	2.75°BSP	1000RPM	2.5°BSP	330Kg/440Kg 1100x1300x1250 1.78M
SRS H/30	30Kg.	700x300 115 Lts	1000RPM	3.75°BSP	1000RPM	2.5°BSP	400Kg/560Kg 1240x1440x1300 2.32M
SRS H/60	60Kg.	1000x300 235 Lts	750RPM	7.5°BSP	750RPM	3° BSP	840Kg/1075Kg 1550x1850x1350 3.87M



aundry care system



SRS Industrial Drying Tumblers

- Stainless steel inner basket "Double walled glass wool insulated outer body duly painted. Electrically interlocked loading & Unloading door "No space required on sides of the machine.
- Electrically Controlled protection provided for auto timing, auto reversing and
 Auto digital temperature controls "protective device against single and reverse
- phasing and motor overload.All controls front displayed with pilot lamps.
- V-Belt and pulley drive for low torgue and high speed.
- Steam radiator/Electric heaters: Made out of coils and aluminum fins for
- Steam heated, & fin type air heating elements for electrically heated machine.
- Centrifugally balanced suction blower mounted directly on to the motor.
- Electric, Steam or thermal fluid heated.

					Heating	J				
Model	Capacity dry wt per Charge	Basket Size Volume	Drive Motor Blower Motor	Main Door Opening	Steam Connection Consumption	Electric Lood	Thermal Fluid Connection Comsuption	Diesel Consumption	Overall Dimension WxDxH APP	Net wt/Shipping Wt. Shipping Size WxDxH App.Shpping Vol.
SRS DT/15	15Kg.	800x600 300Lts	0.37Kw 0.37Kw	500mm	0.5°BSP 25Kg/hr	9kw	0.5°x0.5° BSP 10000Kcal/hr	-	890x1170x1740	295kg/460kg 1190x1470x1940 3.40M
SRS DT/30	30Кд.	950x850 602Lts	0.75Kw 0.75Kw	650mm	0.5°BSP 40Kg/hr	18k	0.5°x0.5° BSP 20000Kcal/hr	2.5 Lts/hr	1050x1460x1980	565kg/1785kg 1350x1450x2150 5.15M
SRS DT/60	60Kg.	1250x99 0 1214Lts	1.5Kw 1.5Kw	800mm	0.5°BSP 80Kg/hr	36kw	1.0°x1.0° BSP 40000Kcal/hr	5 Lts/hr	1350x1690x2300	890kg/1190kg 1350x2000x2500 8.2M
SRS DT/100	100Ka	1600x120 0 2411Lts	15Kw	1000mm	0.5°BSP 150Kg/hr		1.5°x1.5° BSP 80000Kcal/hr	7.5 Lts/hr	1750x2190x2750	1720kg/2190kg 2050x2500x2950 15.12M

SRS Industrial Washer Extractor

- Front, Outer casing, inner basket sides, back & top panels all in full Stainless Steel. A separate compartment chemical dispenser.
- Large Door with Interlock for safety.
- Single Motor Drive. Large capacity motor working with variable.
- Frequency drive speed for wash, distribution, low, normal & high spin.
- Low Power Consumption. "Easy to Operate Space Saving.
- Robust spring suspension system with industrial shock absorbers.
- 350G Extract Force Powerful Advance Microprocessor Control.
- Electric or Steam heated type.

	Capaci ty per	Basket Size Volume	Drive Motor	Basket Speeds		Door	Water	Drain	Heating Steam	Electric	Overall Dimension	Net wt/Shipping Wt. Shipping Size WxDxH
Woder	Charge			Wash	Final Extract	Opening	Connection	brain	Connection	Licettie	WxDxH APP	App. Shipping Vol.
SRS/ We30	30Kg	⊖900x5 00 318Lts	50Kw	35 to 45 RPM	800 RPM	Θ500	Θ25(1.0°BS)	Θ75	Vx30 015(0.5°BSP)	18Kw	W 1350 D 1450 H 1725	1250Kg/1450Kg 1550x1650x1925 4.92M
SRS/ We60	60Кд	⊖1100x6 50 617Lts	10Kw	35 to 45 RPM	720 RPM	Θ650	Θ38(1.5°BS)	Θ75	Vx30 015(0.5°BSP)	36Kw	W 1650 D 1750 H 2025	2250Kg/2550Kg 1800x1950x2250 7.9M
SRS/ We120.	120Kg	Θ1350x8 50	18.5Kw	35 to 45 RPM	650 RPM	Θ800	Θ50(2°BS)	Θ75 2Nos	Vx120 O23(1°BSP)	1	W 1950 D 2050 H 2300	4250Kg/4650Kg 2150x2250x3150 15.2M
SRS/ We120 Forwar d TILT	120Kg	1216lts 01350x8 50 1216Lts	18.5Kw TILT Motor 1.5Kw	35 to 45 RPM	650 RPM	Θ800	Θ50(2°BS)	Θ75 2Nos	Vx120T Θ25(1ºBSP)		W 1520 D 2200 H 2100	4450Kg/4850Kg 2150x2250x3150 15.2M



laundry care system



SRS Vacuum Finishing Table

Large Flat Top padded with imported Silicon padding. Strong welded construction. Thermostatically controlled stainless steel table heater. Extended exhaust duct with lighting device. Adjustable garment hanger stand.

Powerful Suction though centrifugal blower activated by spring loaded full length foot pedal working in conjuction with sturdy microswitch.

Ideal cover material helps achieve excellent ironing results. Silicon iron stand protects ironing and teflon soles with stand upto 150°C of temperature.

Model	Table Top Size	Suction Motor	Suction Capacity	Overall Dimension	Net Wt
SRS / PT	1250x750	400LTS/SEC (850CFM)	1000RPM	1530x890x1850	165 Kg
SRS / PT	1500x900	600LTS/SEC (1300CFM)	1000RPM	1780x1040x1850	190 Kg

SRS Industrial Hot water Boiler

Hot water boiler Heavy duty steam cell, powerfully three side safety valve, diesel fire Heating with diesel tank. Boiler consume diesel 2.5 to 3 liter per hour. Micro display, Italian burner, Fully automatic water cut off, automatic cut off on high temperature. cell 304 SS OUTER BODY SS



aundry care system



SRS Industrial Stain Removing Machine

Stain Removing Machine is manufactured of stainless steel with S.S. Narrow swiveling sleever arm. It is an ecological chemical suction with all electrical. Stain Removing Machine consists of the following features: S.S. Rack for solvent containers. S.S. forged imported spotting guns. Heavy Duty imported steel air gun. Cold and Hot spotting device for pre and post spotting.

0





Industrial Dry Linen Trolley Capacity-50Kg Size-850x650x1650 (WxDxH)



aundry care system

Industrial Dry Linen Trolley Capacity-50Kg Size-850x650x800 (WxDxH)



Industrial Wash Room Trolley Capacity-100Kg Size-850x650x800 (WxDxH)



Industrial Dry Linen Trolley Capacity-50Kg Size-1130x720x800 (WxDxH)

SRS Steam Generator, Electric Fully Automatic

Pressure Vessel:-

Boiler quality steel construction. S.S. heavy duty electrics heaters, imported water level regulator, electric solenoid steam release safety valve, water level gauge, safety release valve.





SR Industrial Diesel fired Steam Boiler (Automatic)

Capacity 250 kg. Heavy duty hot water cell-SS304. Powerfully recirculation pumps heavy duty, three side safety valve, diesel fire Heating with diesel tank. Boiler consume diesel 7 to 8 liter per hour. Italian burner, Fully automatic water cut off, automatic cut off on high temperature. Electrical load-0.75 kw



- Address :- Plot No. 690, Saini Vihar, Firni Road, Village Mundka Delhi - 110041 INDIA
- Mobile No.:- +91-9910904320, +91-9310969390
 - Email:- srsons12@gmail.com
 - Website:- www.srsonsemr.in



